

Instabilities and Taylor dispersion in isothermal binary thin fluid films

Z. Borden,¹ H. Grandjean,² A. E. Hosoi,³ L. Kondic,⁴ and B. S. Tilley^{1,a)}

¹Franklin W. Olin College of Engineering, Needham, Massachusetts 02492, USA

²Ecole Polytechnique, 91128 Palaiseau Cedex, France

³Hatsopoulos Microfluids Laboratory, Massachusetts Institute of Technology, Cambridge, Massachusetts 02139, USA

⁴Department of Mathematical Sciences, Center for Applied Mathematics and Statistics, New Jersey Institute of Technology, Newark, New Jersey 07012, USA

(Received 14 March 2008; accepted 8 September 2008; published online 28 October 2008)

Experiments with glycerol-water thin films flowing down an inclined plane reveal a localized instability that is primarily three dimensional. These transient structures, referred to as “dimples,” appear initially as nearly isotropic depressions on the interface. A linear stability analysis of a binary mixture model in which barodiffusive effects dominate over thermophoresis (i.e., the Soret effect) reveals unstable modes when the components of the mixture have different bulk densities and surface tensions. This instability occurs when Fickian diffusion and Taylor dispersion effects are small, and is driven by solutalcapillary stresses arising from gradients in concentration of one component, across the depth of the film. Qualitative comparison between the experiments and the linear stability results over a wide range of parameters is presented. © 2008 American Institute of Physics. [DOI: 10.1063/1.3005453]

I. INTRODUCTION

Beginning with the fundamental experiments of Kapitza and Kapitza,^{1,2} interfacial phenomena on thin falling liquid films have continually inspired scientific curiosity (see, e.g., Refs. 3–5 and, more recently, Refs. 6 and 7). The progression of traveling-wave solutions, uniform in the spanwise direction but unstable to long-wave three-dimensional disturbances, has been investigated experimentally using mixtures.^{3–5} Mixtures provide a convenient way to vary the material properties of the film and to understand how pattern formation depends on these properties. However, the majority of these experiments are conducted either along a vertical plane, or are driven by a weak hydrostatic jump near the inlet. Furthermore, the mixture is generally expected to be well mixed so that gradients in material properties, such as surface tension, are absent.

Onsager^{8,9} derived a comprehensive derivation of general reciprocity relations that must be satisfied in order for time reversibility to hold. These relations covered a wide range of physical phenomena, including cases involving binary mixtures. A more comprehensive review of the classical development can be found in the text by de Groot and Mazur.¹⁰ It was from this development that Landau and Lifshitz¹¹ formulated a model where the mass flux of one mixture component in a second depends not only on Fickian diffusion but also on temperature and pressure gradients. The sensitivity of mass transport to temperature differences has been well established, but its dependence on pressure differences, to the best of our knowledge, has not been as carefully considered. As described in Ref. 11, in cases where fluid flows are not driven, barodiffusion effects are subdominant

compared to thermophoresis effects. However, Landau and Lifshitz do note that mass transport due to pressure differences can be enhanced when the mixture is driven.

The presence of flow significantly modifies the rate of diffusion of a solute within a solvent. The phenomenon of Taylor dispersion (see Taylor^{12,13}) was originally found in the diffusion of solute in a solution flowing through a thin tube. If the flow profile is the same as Hagen–Poiseuille flow, Taylor discovered that the disturbance concentration of the solute in the solution behaves according to a modified diffusion equation,

$$C_t = \left\{ \frac{1}{\text{Pe}} + \frac{\text{Pe}}{192} \right\} C_{xx},$$

where x is a frame of reference moving with the average flow velocity and Pe is the Peclet number of the solution. The first term is the modified diffusion coefficient corresponding to classical Fickian diffusion, while the latter measures the dispersion of the solute due to the advection in the flow. This result led to the efficient measurement of the diffusion coefficient between solutes and solvents.¹⁴ We note that, although Fickian processes are isotropic, Taylor dispersion of solute in a solvent acts only in the direction of the flow.

Starting from the formulations of Eckhart in 1940,¹⁵ Cahn and Hilliard¹⁶ used a binary mixture formulation along with the Korteweg tensor to model excess pressure effects local to diffuse interfaces. Interest in model representations of binary mixtures grew in the 1990s. Joseph¹⁷ first proposed the notion of quasi-incompressibility in binary mixtures whose components have different bulk densities. Extensions of this model appeared contemporaneously by Anderson *et al.*¹⁸ and Lowengrub and Truskinovsky¹⁹ who focused on the

^{a)}Author to whom correspondence should be addressed. Electronic mail: tilley@olin.edu.



FIG. 1. (Color online) Experimental images showing variation in dimple size. Images are ordered from left to right with 5 s intervals between each frame. The water volume fraction is $\phi=0.3$, and the inclination angle is $\alpha=20^\circ$.

development of interfacial theories proposed initially in Ref. 16. Additional studies of binary mixtures include Refs. 20–24. This potentially bewildering array of models is made possible by the fact that multiple mathematical formulations both conserve energy and ensure that entropy strictly increases.

The focus of current research in this field relates to temperature-driven segregation of mixtures, called thermophoresis or the Soret effect. This effect couples the mass transport and thermal transport of the fluid. Some recent examples of work in this area center on Marangoni–Rayleigh–Bénard convection^{25–29} and the impact of these effects in modeling the behavior of nanofluids.³⁰ However, considerably less attention has been dedicated to isothermal instabilities of binary mixtures.

Figure 1 shows a series of photos illustrating the novel instability addressed herein. As the fluid flows down the incline (from top to bottom in each frame), we observe the formation of “dimples:” three-dimensional instabilities that appear *ab initio* in binary mixtures. The details of the experiments are described in Sec. II. Section III describes the lubrication model based on the approach by Lowengrub and Truskinovsky¹⁹ which results in two coupled evolution equations for the film in the zero Reynolds number limit, describing the interfacial evolution and the local mean concentration of one fluid component. Section IV presents a linear stability analysis of this model, and describes the instability in terms of the product of a barodiffusion coefficient, a difference in specific volume, and a Marangoni number. We discuss the conditions under which this instability may be present, along with the dependence of the wavenumber of the most dangerous mode on inclination angle and Peclet number. Predictions of this model are consistent with reported experimental results. This comparison is discussed in our Sec. V.

II. EXPERIMENT

Figure 2 shows a schematic of the flow apparatus. A mixture of glycerol and water is manually loaded into the upper reservoir to a specified height H . It is then driven by gravity through a 3 cm long channel underneath a gate, adjustable from 0 to 1 cm in height, and emerges onto a film plane 100 cm long and 10 cm wide. The experimental apparatus is supported by two ring stands which adjust the plate to an inclination angle α . For all experimental data presented here, the gate height was set to 0.5 mm.³¹ An experimental run consists of filling the upper reservoir to a height of 8 cm and allowing the fluid to drain to a height of 2 cm. On average, it took ~ 7 min to complete an experimental run, during which time the flow rate decreased slowly. We note that, in a

series of preliminary experiments, we used a pump to transport the mixture from the drainage tank back into the source tank at the top of the inclined region to maintain a constant pressure head. The fluid, however, acquired debris from the pump over time and the level of particulation appeared to be important in the onset of the observed instability. Furthermore, the pump was found to heat the fluid, establishing temperature gradients in the mixture. In order to avoid these effects, we removed the pump and simplified the experiment to the one shown in Fig. 2.

To record the local thickness profile of the film over time, we utilize a fluorescence imaging system developed by Liu *et al.*³ The mixture consisted of water and Acros Organic 99% synthetic glycerol. The fluid is then doped with a small concentration of fluorescein ($\frac{1}{16}$ g/l) which fluoresces under ultraviolet illumination. The composition of the mixture is defined by water volume fraction which varies from $\phi=0$ to $\phi=1$. Water and glycerol have different indices of refraction, so any sharp concentration gradients are visually detectable. No quantitative measurement was made to resolve the mixing concentrations further. The water and glycerol were stirred using a magnetic bar stir until all fluorescein was dissolved and no concentration gradients were observed. Solutions stored for longer than a few hours were remixed before use. The respective physical properties of water and glycerol are shown in Table I. For sufficiently thin films (1 mm or thinner), we find a linear relationship between intensity and film thickness given by

$$I(x, y, t) = KI_0(x, y)h(x, y, t), \quad (1)$$

where $I_0(x, y)$ describes the illumination field as a function of UV source positioning and K is a constant. The function $I_0(x, y)$ is measured for a stable film. To determine K , a vessel with known cross-sectional area is filled with known volumes of fluid and imaged.




FIG. 2. Schematic of the falling thin film flow apparatus with variable inclination angle α , showing the manually variable gate used to control film height and the measurement method based on fluorescent imaging.

TABLE I. Physical properties of pure substances used in the mixture. The volume fraction $\phi=0$ corresponds to pure glycerol and $\phi=1$ to pure water. Glycerol properties were obtained from the manufacturer (Acros Organics).

	Water ($\phi=1$)	Glycerol ($\phi=0$)
Density	$\rho_w=1 \text{ g/cm}^3$	$\rho_g=1.261 \text{ g/cm}^3$
Surface tension	$\gamma_w=72 \text{ dynes/cm}$	$\gamma_g=64 \text{ dynes/cm}$
Viscosity	$\mu_w=0.89 \text{ cP}$	$\mu_g=1069 \text{ cP}$

After a flowing film is established on the inclined plane, small transient localized depressions are observed scattered across the film surface. These depressions, referred to as “dimples,” are reminiscent of the surface of a puddle during a rainstorm (see Fig. 1) with the exception that no driving mechanisms (such as raindrops) are readily evident. Figure 3 shows the results of fluorescence imaging of individual dimples. The figure reveals that the initial shape of the dimple is conical with a length to width aspect ratio of about 2:1. This aspect ratio changes rapidly during its initial non-linear evolution, and is slightly modified during relaxation. High speed imaging shows that formation occurs on a time scale approximately ten times faster than relaxation. The interfacial profile in the plane along the centerline of the dimple is shown in Fig. 4. From this figure, we can estimate the error in our experimental technique using the magnitude of the oscillations that appear before and after the dimple.

Observed dimples range in size from 1 to 20 mm in diameter and exist for $\sim 0.1\text{--}1.5 \text{ s}$. Since the instability time scale is much smaller than the transient behavior in the overall flow, we consider the global flow to be quasistatic with respect to the instability. Due to limitations of the optical equipment, we are not able to resolve dimples smaller than 3 mm in diameter. The variation in size is roughly illustrated in Fig. 1, which shows the distribution of dimples in several images from one experimental run.

In Fig. 5, we show the locations of dimple formation over the entire pitch of the plate for ten experimental runs carried out under identical experimental conditions. The majority of dimples appear near the gate region. The slight increase in dimple concentration at the bottom of this image is due to improved resolution near the lower portion of the graph and reflects the location of the light source. Notice, however, that the dimples do not preferably form at any par-




FIG. 4. (Color online) (a) Experimentally measured cross-sectional profile of a typical dimple during formation at $\frac{1}{30} \text{ s}$ intervals for $\alpha=20^\circ$ and $\phi=0.4$. (b) Two dimensional profile of same dimple during dissipation at $\frac{1}{3} \text{ s}$ intervals. Lateral peak movement is due to flow advection.

ticular location, suggesting that plate imperfections are not a driving factor in dimple formation.

Dimples were only observed in binary mixtures—they were not observed in experimental trials involving pure water or pure glycerol. In order to understand the influence of the water volume fraction on the frequency of dimpling, several experiments were carried out using solutions characterized by water volume fractions of $\phi=0.4$, $\phi=0.5$, and $\phi=0.6$. It is important to note that a change in ϕ simultaneously affects the concentration, viscosity, surface tension, and density of the mixture.

Several experimental trials were conducted to rule out potential mechanisms for dimple formation. We considered the possibility that shear forces in the film were causing a buildup of charge in the fluid itself or on the substrate. Such nonuniform charge distributions could lead to local deformations of the interface. However, when the channel and the collection reservoir were coated with a conductive material and grounded, dimples were still observed. We also observe a random distribution of the dimples across the plate, suggesting that liquid-solid interaction energy (and its spatial dependence on local inhomogeneities in the substrate) is not a source of instability. Finally, the film thicknesses at which dimples are observed (on the order of a millimeter) are orders of magnitude too thick for van der Waals forces to be significant.

The frequency of dimples also appears to depend on the flow rate of the film. As the reservoir drains, the rate of the appearance of this instability decreases with decreasing the flow rate. This suggests that the presence of a sufficient flow field is important in the development of these structures.




FIG. 3. (Color online) (Top) Three-dimensional profile of a typical dimple during formation at $\frac{1}{60} \text{ s}$ intervals for $\alpha=20^\circ$ and $\phi=0.4$. Notice the dimple’s 2:1 length to width aspect ratio. (Bottom) Three-dimensional profile of a typical dimple during relaxation at $\frac{1}{6} \text{ s}$ intervals for $\alpha=20^\circ$ and $\phi=0.4$. The aspect ratio deformation is due to flow advection. The shades of gray indicate films thickness. The spectrum bar units are in millimeters.




FIG. 5. (Color online) Spatial locations of dimple formations over ten 4 min runs. The dashed region is the focus of our linear stability analysis.

III. LUBRICATION MODEL

In light of the fact that a binary mixture is required to drive the instability and the lack of any significant temperature gradients in our system, we propose a model that includes the effects of pressure gradients in the mass transport of solute. This effect, called barodiffusion by Landau and Lifschitz,¹¹ is usually masked by the Soret effect when temperature fluctuations are present. The effect is pertinent when the densities of the component fluids are different (see Refs. 17–19). Hydrostatic pressure within the film triggers this barodiffusive effect and establishes a concentration gradient normal to the inclined plane. If one of the components contains surface active agents, then these concentration gradients can lead to surface-tension gradients in the film. In this work, we show that instabilities occur when the stabilizing effects of Fickian diffusion and Taylor dispersion are small, and that the instability is primarily three dimensional. We anticipate that the critical requirement for this instability to occur is the presence of a vertical concentration gradient of the component fluids. Barodiffusion, used here, is one potential mechanism that can be exploited to create such a gradient, but other mechanisms (such as evaporation³²) may be possible.

Consider the motion of an isothermal thin liquid film of a two component fluid flowing down an inclined plane. The components have different bulk densities, ρ_1, ρ_2 and different surface tensions in their pure phases, γ_1, γ_2 . To compare the results of our model with the experiment, we associate quantities with subscript 1 with glycerol and those with 2 with the bulk values for water. We note that if we have a particular mass fraction of glycerol C in the mixture then we can represent the density as

$$\frac{1}{\rho} = \frac{1}{\rho_1}C + \frac{1}{\rho_2}(1 - C).$$

In the following, the kinematic viscosity of the mixture is determined by the relation found in Ref. 33,

$$\ln \nu = X \ln \nu_w + (1 - X) \ln \nu_g + GX(1 - X), \quad (2)$$

where X is the molar fraction of water and G is an empirically determined parameter.

Finally, we assume that the surface tension can be written in the form

$$\gamma(C) = \gamma_1 + (\gamma_2 - \gamma_1)(1 - C).$$

Note that in the experiment, surface reagents are known to exist in the manufacture of glycerol. These reagents remain attached to the glycerol proper, and need not be modeled separately from the distribution of glycerol. The presence of these reagents would simply change the value of γ_1 in our expression for surface tension.

To model conservation of mass, momentum, and water mass fraction, we use the following expressions, found in Lowengrub and Truskinovsky:¹⁹

$$\rho \frac{DC}{Dt} = \frac{\rho_1 \rho_2}{\rho_2 - \rho_1} \nabla \cdot \mathbf{u}, \quad (3)$$

$$\rho \frac{D\mathbf{u}}{Dt} = -\nabla p + \rho \mathbf{g} + \nabla \cdot \{\mu(\nabla \mathbf{u} + \nabla \mathbf{u}^T)\}, \quad (4)$$

$$\rho \frac{DC}{Dt} = -\nabla \cdot \mathbf{J}, \quad (5)$$

where $\mathbf{u} = (u, w)$ is the fluid velocity of the mixture, \mathbf{g} is the gravitational vector, and μ is the dynamic viscosity of the mixture which depends on the local concentration. The first two equations represent conservation of mass and momentum, respectively, of the mixture; the final equation reflects mass conservation for one of the components. The mass flux \mathbf{J} depends on solutal diffusion of the water and on the local pressure variation

$$\mathbf{J} = -\rho D \left\{ \nabla C - \frac{1}{P_o} \left(\frac{1}{\rho} \frac{\partial \rho}{\partial C} [\nabla p] \right) \right\}, \quad (6)$$

where P_o is the ambient pressure. The coefficient in front of the pressure gradient in Eq. (6) is called the *barodiffusion coefficient*.¹¹ For glycerol in water, we use the value of the diffusion coefficient as $D \approx 10^{-4}$ cm²/s. This value was not measured for our particular system, but the estimate falls within the range for typical glycerol products (e.g., see Ref. 34).

The form of this mass flux shows the driving mechanism of the instability. Formally, if we substitute Eq. (6) into Eq. (5), we find that

$$\rho \frac{DC}{Dt} = D \{ \nabla \cdot [\rho \nabla C] \} + B \{ \nabla \cdot [\rho \nabla p] \}.$$

Hence, if pressure gradients are nonuniform spatially, then segregation in the concentration field C can occur on a scale determined by the coupling coefficient B . The analysis below focuses on values of B that are small.

We note that the focus of Ref. 19 centered on using a mixture theory, along with additional Korteweg stresses, which depend on sharp density variations to describe added normal stresses found in the interfacial region between two fluids. The interfacial length scales in question are on the order of tens of nanometers. Since the smallest length scale in our problem is on the order of tens of microns, we neglect the Korteweg stress terms *a priori* in the modeling. One can

formally show that these effects are higher order in the asymptotic analysis below.

Along the plate, the no-slip boundary condition is applied along with no mass flux: $\mathbf{u}=0$, $\mathbf{J}\cdot\mathbf{k}=0$ at $z=0$. At the free surface $z=h(x,t)$, we assume that the kinematic boundary condition applies, shear stress along the film is balanced by surface-tension gradients, normal stress is balanced by capillary forces, and there is no mass flux across the interface

$$h_t + uh_x - w = 0, \quad (7)$$

$$\mathbf{t} \cdot \mathbf{T} \cdot \mathbf{n} = \nabla \gamma \cdot \mathbf{t}, \quad (8)$$

$$\mathbf{n} \cdot \mathbf{T} \cdot \mathbf{n} = \gamma \kappa, \quad (9)$$

$$\mathbf{J} \cdot \mathbf{n} = 0, \quad (10)$$

where \mathbf{T} is the stress tensor

$$\mathbf{T} = -\left(p + \frac{2}{3}\mu \nabla \cdot \mathbf{u}\right)\mathbf{I} + \mu(\nabla\mathbf{u} + \nabla\mathbf{u}^T).$$

We apply the following scales to nondimensionalize the system near the mean concentration $C=C_o$:

$$[x] = L \equiv \sqrt{\gamma_o/(\rho_o g)}, \quad [z] = H, \quad [t] = L/U,$$

$$[u, w] = (U, \epsilon U), \quad [\rho] = \rho_o = \rho(C_o), \quad [p] = \rho_o g H,$$

where L is the capillary length, $\gamma_o = \gamma(C_o)$ is the surface tension at the concentration C_o , $\epsilon = H/L \ll 1$ is the aspect ratio of the film height to the capillary length, and $U = gH^2/\nu_o$ is the characteristic velocity scale. This scaling is applied to Eqs. (3)–(10) (see Appendix for details). The barodiffusion term is balanced with the remaining terms in the single component mass conservation equation using

$$C = C_o + \epsilon^2 c(x, z, t), \quad \rho = \frac{1}{1 + \epsilon^2 V c(x, z, t)},$$

which leads to the following scaled equations (the terms up to $O(\epsilon^2)$ are retained)

$$\epsilon^2 V \rho(c) \{c_t + uc_x + wc_z\} = u_x + w_z, \quad (11)$$

$$0 = -\epsilon p_x + \rho(c) \sin \alpha + \left\{ (\mu u_z)_z + \epsilon^2 \left[(\mu u_x)_x + \frac{1}{3} ((\mu(u_x + w_z))_x) \right] \right\}, \quad (12)$$

$$0 = -p_z - \rho(c) \cos \alpha + \left\{ (\mu w_z)_z + \frac{1}{3} (\mu(u_x + w_z)_z) + \epsilon^2 (\mu w_x)_x \right\}, \quad (13)$$

$$\epsilon \rho(c) [c_t + \mathbf{u} \cdot \nabla c] = \frac{1}{\text{Pe}} \left\{ [\rho(c) c_z]_z + \beta V [\rho(c) p_z]_z \right\} + \frac{\epsilon^2}{\text{Pe}} \left\{ (\rho(c) c_x)_x + \beta V [\rho(c) p_x]_x \right\}, \quad (14)$$

Here $V = \rho_o(1/\rho_1 - 1/\rho_2)$ measures the difference in specific volumes of the two components, $\text{Pe} = UH/D = gH^3/(\nu_o D)$ is the Peclet number of the mixture, and $\epsilon^2 \beta = \rho_o g H / P_o$, $\beta = O(1)$ is the ratio of the hydrostatic pressure of the mixture to the ambient pressure. In the following we have assumed negligible inertial effects, i.e., we consider $\text{Re} = gH^3/\nu_o^2 \ll \epsilon$.

However, $\text{Pe} \neq 0$, so we retain advection in the solute equation.

The rescaled boundary conditions at $z=0$ become

$$u = w = 0 \quad [c_z + p_z + \rho \cos \alpha] = 0 \quad (15)$$

and at the free surface, $z=h(x,t)$:

$$h_t + uh_x = w, \quad (16)$$

$$(u_z + \epsilon^2 w_x)(1 - \epsilon^2 h_x^2) - 4\epsilon^2 u_x h_x = \epsilon M [c_x + h_x c_z] N, \\ -p - \frac{2}{3} \epsilon (u_x + w_z) + \frac{2\epsilon}{N^2} \{w_z(1 - \epsilon^2 h_x^2) - h_x(u_z + \epsilon^2 w_x)\} \\ = (1 + \epsilon^2 M c) \frac{h_{xx}}{N^3}, \quad (17)$$

$$\{(c_z - \epsilon^2 h_x c_x) + \beta V(p_z - \epsilon^2 p_x h_x)\} = 0, \quad (18)$$

where $N = \sqrt{1 + \epsilon^2 h_x^2}$ and $M = (\gamma_1 - \gamma_2)/(\gamma_o)$ is the Marangoni parameter.³⁵ Note that for glycerol and water, $V < 0$ and $M < 0$.

To solve this system, we use lubrication theory. Let us assume that all of the remaining dimensionless groups are $O(1)$. We expand

$$u = u_o + \epsilon u_1 + \epsilon^2 u_2 + \dots,$$

$$w = w_o + \epsilon w_1 + \epsilon^2 w_2 + \dots,$$

$$c = c_o + \epsilon c_1 + \epsilon^2 c_2 + \dots,$$

$$p = p_o + \epsilon p_1 + \epsilon^2 p_2 + \dots.$$

The equations and boundary conditions above can be solved to find velocities, pressures, and concentrations to order ϵ which are given in Appendix. It is useful to note that the single component conservation equation becomes $c_{oz} = -\beta V p_{oz} = \beta V \cos \alpha$, which gives $c_o = z\beta V \cos \alpha + \bar{c}_o(x, t)$, showing that hydrostatics does indeed induce a concentration gradient in the film. Physically, the leading-order disturbance concentration can be decomposed into two terms: The first corresponds to the effects of barodiffusion, while the second corresponds to an unknown average disturbance concentration. Note that each correction to the disturbance concentration has a component that is independent of z , since the mass flux of the component is zero along the plate and the free surface. The goal of the analysis that follows is to find the evolution equation for this average disturbance concentration, which depends on the local interfacial shape. Combining conservation of mass with the velocities, and using Eq. (A7) in the Appendix, we arrive at the following equation for the evolution of the film thickness:

$$h_t + h^2 h_x \sin \alpha + \epsilon \left\{ \frac{h^3}{3} [h_{xxx} - \cos \alpha h_x] + M \frac{h^2}{2} [\bar{c}_x + \beta V h_x \cos \alpha] \right\}_x = O(\epsilon^2). \quad (19)$$

which for $\beta=0$ reduces to the standard solutal capillarity interfacial equation.

Equation (20) must be coupled with an evolution equation for concentration, \bar{c} . To find the equation of motion for the concentration \bar{c}_1 , we need to consider Eq. (14) at $O(\epsilon^2)$. Integrating Eq. (14) from $z=0$ to $z=h$ we find

$$\begin{aligned} & \frac{1}{\text{Pe}} [c_{2z} + \beta V(p_{2z})]_0^h + \frac{1}{\text{Pe}} [h\bar{c}_{\text{ox}x} + hp_{\text{ox}x}] \\ &= \int_0^h c_{1t} + u_o c_{1x} + w_o c_{1z} dz \\ &+ \left\{ \frac{h^3}{3} [-p_{\text{ox}}] M \frac{h^2}{2} [\bar{c}_{\text{ox}} + \beta V h_x \cos \alpha] \right\} \bar{c}_{\text{ox}} \end{aligned}$$

and

$$\begin{aligned} & \int_0^h c_{1t} + u_o c_{1x} + w_o c_{1z} dz \\ &= -\frac{7}{24} \beta V \sin^2 \alpha [(h^4 h_x)_x] \\ &+ \frac{\text{Pe} \beta V \sin^2 \alpha \cos \alpha}{3024} \{2h^7 h_{xx} - 161h^6 h_x^2\} \\ &- \frac{\text{Pe} \sin^2 \alpha}{7560} \{121h^7 \bar{c}_{\text{ox}x} - 238h^6 h_x \bar{c}_{\text{ox}}\}. \end{aligned} \tag{20}$$

A discussion of the different terms in Eq. (20) is useful here. The first term on the right hand side corresponds to the barodiffusion component, resulting from the $w_o c_{1z}$ term. The second term corresponds to the advection induced by the inhomogeneous term in Eq. (A6). The final, stabilizing term arises from Taylor dispersion in a nonuniform film with zero shear stress along the free surface. Note that these effects are acting only in the x -direction and are due to the presence of the base-state flow. To extend this study to higher dimensions, we note that capillarity, solutalcapillarity, and Fickian diffusion are isotropic processes, and the spatial derivative terms in Eq. (20) for these processes are represented by ∇ in the three-dimensional extension below (analogous to a similar extension of a Benney formulation of a single component thin film to three dimensions found in Ref. 36). Further, we collect the \bar{c}_1 terms with the \bar{c}_o terms and drop the bar notation for the z independent component of the disturbance concentration field (i.e., $\bar{c} = \bar{c}_o + \epsilon \bar{c}_1$) at leading order. We find the final depth averaged governing equations for film thickness and concentration,

$$\begin{aligned} & h_t + h^2 h_x \sin \alpha + \epsilon \nabla \cdot \left\{ \left[\frac{h^3}{3} \nabla [\nabla^2 h - \cos \alpha h] \right. \right. \\ & \left. \left. + M \frac{h^2}{2} \nabla [c + \beta V h \cos \alpha] \right\} = 0, \end{aligned} \tag{21}$$

$$\begin{aligned} & c_t + \frac{h^2}{3} \sin \alpha c_x - \frac{\beta V h^2 h_x \sin 2\alpha}{12} = -\epsilon \left\{ \frac{h^2}{3} \nabla [\nabla^2 h - h \cos \alpha] + M \frac{h}{2} \nabla [c + \beta V h \cos \alpha] \right\} \cdot \nabla c \\ &+ \underbrace{\epsilon \frac{\text{Pe} \sin^2 \alpha}{7560} \{121h^6 c_{xx} - 238h^5 h_x c_x\}}_{\text{Taylor dispersion}} + \epsilon \frac{7\beta V \sin^2 \alpha}{24} \{h^3 h_{xx} + 4h^2 h_x^2\} \\ &- \epsilon \frac{\text{Pe} \beta V \sin^2 \alpha \cos \alpha}{3024} \{2h^6 h_{xx} - 161h^5 h_x^2\} + \underbrace{\frac{\epsilon}{h\text{Pe}} \nabla \cdot \{h \nabla c + \beta V [h \nabla p_o]\}}_{\text{Fickian diffusion}}. \end{aligned} \tag{22}$$

IV. LINEAR STABILITY THEORY

We consider the linear stability of the exact solution to Eqs. (21) and (22), $h=1$, and $c=0$, using a standard normal-mode analysis. Assume a deviation of this base state of the form

$$\begin{pmatrix} h(x,y,t) \\ c(x,y,t) \end{pmatrix} = \begin{pmatrix} 1 \\ 0 \end{pmatrix} + \delta \begin{pmatrix} \hat{H} \\ \hat{C} \end{pmatrix} e^{\sigma t + i\mathbf{k} \cdot \mathbf{x}}, \tag{23}$$

where $\delta \ll 1$ is an infinitesimally small amplitude, σ is the growth rate of the disturbance, $\mathbf{k} = (k_x, k_y)$ is the wavenumber vector, and $\mathbf{x} = (x, y)$ is the spatial location along the plate. We assume disturbances that are 2π -periodic in both x and y .

Applying form (23) to the system of Eqs. (21) and (22) and keeping only terms that are linear in δ leads to the following algebraic system:

$$\begin{pmatrix} \sigma + ia_{11} + \epsilon b_{11} & \epsilon b_{12} \\ \beta V \{ia_{21} + \epsilon b_{21}\} & \sigma + \frac{i}{3} a_{11} + \epsilon b_{22} \end{pmatrix} \begin{pmatrix} \hat{H} \\ \hat{C} \end{pmatrix} = \begin{pmatrix} 0 \\ 0 \end{pmatrix}, \tag{24}$$

where the coefficients $a_{11}, b_{12}, b_{21}, b_{22}$ are given by

$$\begin{aligned} & a_{11} = k_x \sin \alpha, \\ & b_{11} = \left\{ |\mathbf{k}|^2 \left[\left(\frac{1}{3} - \frac{\beta VM}{2} \right) \cos \alpha + \frac{|\mathbf{k}|^2}{3} \right] \right\}, \end{aligned}$$

$$b_{12} = -\frac{M}{2}|\mathbf{k}|^2,$$

$$a_{21} = -\frac{k_x \sin 2\alpha}{12},$$

$$b_{21} = \left\{ \frac{7}{24}k_x^2 \sin^2 \alpha - \frac{\text{Pe} k_x^2 \sin^2 \alpha \cos \alpha}{1512} + \frac{|\mathbf{k}|^2(\cos \alpha + |\mathbf{k}|^2)}{\text{Pe}} \right\},$$

$$b_{22} = \left\{ \frac{121}{7560}\text{Pe} k_x^2 \sin^2 \alpha + \frac{|\mathbf{k}|^2}{\text{Pe}} \right\}.$$

Note that a_{11} , a_{12} , and b_{22} are positive, and $b_{12} < 0$. However, b_{21} can be of either sign, representing the competition between linear barodiffusive effects and the advective terms induced by the flow and the concentration gradient in z .

To find the dispersion relation, we set the determinant of the matrix in Eq. (24) to zero, and find the growth rates σ . It is instructive, however, to consider first the case with no barodiffusion, namely, $\beta=0$. In this case, system (24) is upper triangular, and the growth rates are given by the requirement that the diagonal elements vanish,

$$\sigma_{oh} = -\epsilon \left\{ |\mathbf{k}|^2 \left[\frac{1}{3} \cos \alpha + \frac{|\mathbf{k}|^2}{3} \right] \right\} - ik_x \sin \alpha, \quad (25)$$

$$\sigma_{oc} = -\epsilon \left\{ \frac{121}{7560}\text{Pe} k_x^2 \sin^2 \alpha + \frac{|\mathbf{k}|^2}{\text{Pe}} \right\} - \frac{ik_x \sin \alpha}{3}. \quad (26)$$

Equation (25) is the standard dispersion relation for a single-phase film falling down an inclined plane.⁵ Since inertial effects are neglected, this mode remains stable. Similarly, Eq. (26) reflects stability through both Fickian diffusion and Taylor dispersion. Thus the interfacial growth rate σ_{oh} evolves independently of the solutal concentration σ_{oc} .

Let σ_h and σ_c correspond to the growth rates of the interfacial and of the concentration mode, respectively. Consider the case when β is small, and assume that $\sigma_c = \sigma_{oc} + \beta\sigma_{1c} + \dots$. If we then solve for the real part of σ_{1c} through an asymptotic expansion of the dispersion relation for small β , we find that

$$\begin{aligned} \text{Re}(\sigma_{1c}) &= \frac{Vb_{12}}{\sigma_{oc} - \sigma_{oh}} \{ia_{21} + \epsilon b_{21}\} \\ &= \epsilon \frac{|\mathbf{k}|^2 MV}{2|\sigma_{oc} - \sigma_{oh}|^2} \left\{ \frac{1}{18}k_x^2 \sin \alpha \sin 2\alpha + O(\epsilon^2) \right\}. \end{aligned}$$

Since $M < 0, V < 0$, the real part of σ_1 is positive; if we are near the solutal stability criterion, $\sigma_{oc} \approx 0$, the mode of instability will depend on the solutalcapillarity effect M between the two components of the mixture. Note that this instability is not present if the components have equal density ($V=0$). Thus, if σ_{oc} is small, with $\text{Pe} \gg 1$ and $k_x \ll 1$, for example, then barodiffusion can act with solutalcapillarity to induce an instability. This régime corresponds to the case

when both Taylor dispersion and Fickian diffusion effects are small. Note that the eigenvector associated with σ_c , (\hat{H}_c, \hat{C}_c) , has a component for which $\hat{H}_c \neq 0$. Hence, even though the instability arises due to changes in the concentration field, the interfacial response need not be zero.

We note that for values of $\beta MV > 2/3$ the density mismatch of the bulk component fluids and solutocapillarity are sufficiently strong to overcome the stabilizing effects of hydrostatic pressure in the interfacial Eq. (21). Since this effect is not seen in our experiments, we use the following as an upper bound on β :

$$\beta MV < \frac{2}{3}.$$

We explore how the wavenumber of the maximum growth rate varies with Pe and with β . In Fig. 6 we show the real part of the growth rate of the disturbance for the concentration mode σ_c . Each subfigure corresponds to a contour plot with $0 \leq k_x \leq 3/2$ and $0 \leq k_y \leq 3$. We keep V, M fixed as in Table II. The colors correspond to the growth rate, with (dark) green being stable, (gray) yellow-green being neutrally stable, and (light) yellow being more unstable. Note that the interfacial mode remains stable for all of the values of β and Pe considered, and the stability behavior is not sensitive to these parameters.

However, the stability of the concentration mode shown in Fig. 6 does depend on the values of β and Pe . For $\beta=0$, we note that the stability in the x -direction is enhanced by Taylor dispersion as Pe increases. Increasing Pe reduces the effect of Fickian diffusion, leading to the elliptical contours found for $\text{Pe}=400$. As the barodiffusion coefficient β increases, a mode of instability develops for sufficiently high Pe . The wavevector of the disturbance (k_x, k_y) is oblique to the flow. Due to the symmetry in the y -coordinate, the disturbance with wavenumber $(k_x, -k_y)$ is also unstable under the same conditions, thus any superposition of these two unstable modes is itself unstable with the same growth rate. One example of such a superposition is given in Fig. 7. Note that the interfacial deflection (shown by the meshed surface) is deformed in a different pattern than is seen in the concentration field shown with the color contour plot along the $z=0$ axis.

To confirm our understanding of the physical onset of this instability, we explore how the wavenumber of the maximum growth rate varies with Pe and β . We consider $\beta=1, 2, 3$ and note that the stability depends on the product βMV . Hence the instability does not occur for mixtures which have the same density, even if soluble surface acting agents are present. Figure 8 (top) shows how the growth rate varies with Pe for $\beta=1, 2, 3$. Notice that the instability is present for $\text{Pe} > \text{Pe}_c=41$ for $\beta=1$, and for $\text{Pe} > \text{Pe}_c=15$ for $\beta=3$. In the lower plot in Fig. 8, we show the locus of wavenumbers for the mode with the maximal growth rate. As $\text{Pe} \rightarrow \text{Pe}_c$, the wavenumber of the maximally growing mode approaches the origin in this plane.

Figure 9 shows the influence of the inclination angle α on the stability properties. From Fig. 9(a), we note that the instability vanishes for sufficiently large angles. The angle at which this mode restabilizes increases for larger values of β .




FIG. 6. (Color online) Contour plot of the concentration mode $\text{Re}\{\sigma_c\}$ for $\beta = 0, 1, 2, 3$ and $\text{Pe} = 1, 200, 400$. The x - and y -axes correspond to the x - and y -component of the wavevector, respectively. Note that $M = -1$, $V = -0.2$, $\alpha = 10^\circ$, and $\text{Re} = 0$.

For sufficiently small values of α , we see that the instability becomes two dimensional, as can be seen in expanded regions, highlighted in the lower graphs of Figs. 9(a) and 9(b). Notice that near this region, we can find angles at which the wavelengths in the x and y direction are comparable. Finally, we note that as $\alpha \rightarrow \pi/2$, the x -component of the wavenumber becomes quite small compared the y -component. We speculate that the disparate aspect ratio of the elliptical form of the instability may play a role in the formation of rivulets in multicomponent films.

V. CONCLUSIONS

A. Comparison with experiments

The linear stability analysis of the long-wave model [(21) and (22)] captures several features which appear in the experiments. First, we note that the instability appears only for $\beta VM \neq 0$, and appears to grow more quickly with increasing β . This is consistent with the appearance of dimples in Fig. 5. Due to the hydrostatics of the *reservoir*, vertical concentration gradients near the inlet are potentially an order

of magnitude larger than those in the film further down the pitch. Due to the change in shear stress from under the gate to the free surface, the interfacial thickness grows to preserve the volumetric flow rate. Since the vertical velocity is proportional to h_x , and the instability is proportional to β , the linear stability theory presented above suggests an unstable film near the inlet. This result is consistent with the localization of the dimples near the inlet of the film. We expect that the instability enhances mixing of the solution, resulting in a restabilization of the film, with vertical concentration gradients dictated by the mean film thickness.

Second, the growth rates predicted in the model are on the order of $10^{-4} - 10^{-3}$ in dimensionless form. This suggests growth time scales on the order of $10^3 - 10^4$. Our time scale $L/U \approx 30$ s, if we use $\epsilon = 0.01$ as above. Thus, the times for

TABLE II. Table of dimensionless variables.

Dimensionless parameter	Definition	Experimental range	Model range
ϵ	H/L	$10^{-2} - 10^{-1}$	$10^{-3} - 10^{-2}$
Re	gH^3/ν_2	10^{-4}	0
Pe	$gH^3/(\nu_2 D)$	$O(100)$	100–500
β	$\rho_o g L^2 / (P_o H)$	$10^{-2} - 1$	1–10
V	$\rho_o(\rho_2 - \rho_1) / ((\rho_1 \rho_2))$	$-1/5$	$O(1)$
M	$(\gamma_2 - \gamma_1) / \gamma_o$	-1	$O(1)$




FIG. 7. (Color online) Physical shape of the sum of two oblique waves ($k_x, \pm k_y$) for the unstable concentration mode. The interfacial shape is shown in the surface plot (lines), while the concentration field is displayed in the contour plot along the $z=0$ plane. $V = -0.2$, $M = -1$, $\text{Pe} = 200$, and $\beta = 3$.




FIG. 8. (Color online) (Top) Growth rate of concentration mode as a function of Pe for $V=-0.2$, $M=-1$, $Re=0$, and $\alpha=10^\circ$ for $\beta=1$ (solid curve), $\beta=2$ (dashed curve), and $\beta=3$ (dashed-dot curve). Note that the mode becomes unstable for $Pe > Pe_c$. (Bottom) Wavenumber locus $(k_{x,\max}, k_{y,\max})$ for maximally growing concentration mode as a parametric function of Pe for $\beta=1, 2, 3$.

an observable instability are quite long. However, the characteristic speed of the concentration mode $U/3 \approx 30 \mu\text{m/s}$, which translates to an instability occurring within 1 m down the pitch. This is again on the same order of magnitude as the experiment if we consider the dimples that appear far from the inlet (see the boxed region in Fig. 5).

Third, we note that the initial disturbance shown in Fig. 3 evolves to an elliptical shape with the streamwise wavelength $L_x > L_y$. This corresponds qualitatively to the linear stability theory where $k_x < k_y$. Note that the capillary length scale for our system is around 3 mm, so the dimensional lengths shown in Fig. 7 correspond to $L_x \approx 2.5$ cm and $L_y \approx 9$ mm. Again, the experimental data shown in Fig. 3 (second frame) appear consistent with our model. We note that spatial-temporal resolution in the experiments is such that we do not observe dimple translation during its evolution.

B. Discussion

An isotropic instability for thin binary fluid mixtures flowing down an inclined plane under isothermal conditions is reported. The instability occurs owing to pressure gradients which drive mass fluxes. If the components of the mixture have different densities ($V \neq 0$), these component fluxes are not equal, driving segregation and hence, gradients in concentration. Furthermore, if the two components have different surface tensions ($M \neq 0$), gradients in concentration will lead to Marangoni convection. The instability may be enhanced by the presence of a glycerol-soluble surface reagent that is present in the manufacture of glycerol.

We propose a model based on solutalcapillarity and barodiffusion of binary mixtures valid in a long-wave regime. A linear stability analysis of this model lends insight into the onset of the instability observed in the experiment over a wide range of parameter values. The key aspects of the instability require that both Fickian diffusion and Taylor dispersion are small, the component fluids have different surface tensions and bulk densities, and that concentration gradients on the scale of barodiffusive effects are present. Large Peclet numbers and long waves mitigate Fickian diffusion and Taylor dispersion hence, advection is necessary for the instability to occur. We note that our analysis is carried out assuming infinitesimal perturbations, and therefore describes onset, but not the complete evolution of a dimple, including growth saturation which could be expected due to nonlinear effects.

Although we have identified a potential mechanism for the onset of dimples, the form of the dispersion relation suggests that different physical mechanisms could yield a similar instability. For example, the adsorption of water by glycerol may also play a role in developing concentration gradients of glycerol perpendicular to the plane. The presence of this vertical concentration gradient, regardless of how it is generated, is a key for the onset of the instability. In our model, barodiffusion is the mechanism which drives the formation of this gradient. Other possible mechanisms, such




FIG. 9. (Color online) (a) Growth rate of concentration mode as a function of α for $Pe=500$, $V=-0.2$, $M=-1$, $Re=0$, and $\beta=1$ (solid curve), $\beta=2$ (dashed curve), and $\beta=3$ (dashed-dot curve). (b) Wavenumber for maximally growing concentration mode as a function of α . Note that the curves which are larger for $\alpha > 20^\circ$ correspond to $k_{y,\max}$, while the lower curves in this region correspond to $k_{x,\max}$. The lower figures of (a) and (b) show the behavior for $0 < \alpha < 10^\circ$.

as evaporation or the presence of impurities in the fluid, could also set up a response that corresponds to dimples. The possibility that impurities are instigating the instability would suggest that the observations correspond to a response to a localized finite-amplitude disturbance of the film. We leave analyses of this sort for future work.

ACKNOWLEDGMENTS

Z.B. and B.S.T. would like to thank the Research Fund at Olin College for their support, and to M. Jeunette for his fabrication skills of the apparatus. A.E.H. gratefully acknowledges support from the National Science Foundation through Grant No. CCF-0323672. We all would like to thank the participants at the EUROMECH 490 conference for their constructive feedback on an earlier version of this work.

APPENDIX: RESCALED EQUATIONS

In this appendix, we present the nondimensionalized equations and derive the lowest and first-order velocity, pressure, and concentration fields. After applying the scaling and nondimensionalizing the equations of motion, we find that Eqs. (3)–(5) become

$$V\rho(C)\{C_t + uC_x + wC_z\} = u_x + w_z, \quad (\text{A1})$$

$$\begin{aligned} \epsilon\rho(C)\text{Re}\{u_t + uu_x + wu_z\} \\ = -\epsilon p_x + \rho(C)\sin\alpha \\ + \left\{(\mu u_z)_z + \epsilon^2\left[(\mu u_x)_x + \frac{1}{3}((\mu(u_x + w_z))_x)\right]\right\}, \end{aligned} \quad (\text{A2})$$

$$\begin{aligned} \epsilon^2\rho(C)\text{Re}\{w_t + uw_x + ww_z\} \\ = -p_z - \rho(C)\cos\alpha \\ + \epsilon\left\{(\mu w_z)_z + \frac{1}{3}(\mu(u_x + w_z)_z) + \epsilon^2(\mu w_x)_x\right\}, \end{aligned} \quad (\text{A3})$$

$$\begin{aligned} \epsilon\rho(C)[C_t + \mathbf{u} \cdot \nabla C] = \frac{1}{\text{Pe}}\{[\rho(C)C_z]_z + \bar{\beta}V[\rho(C)p_z]_z\} \\ + \frac{\epsilon^2}{\text{Pe}}\{(\rho(C)C_x)_x + \bar{\beta}V(\rho(C)p_x)_x\}. \end{aligned} \quad (\text{A4})$$

We assume that the concentration C is close to an equilibrium value C_o , and that deviations from this concentration are proportional to the barodiffusive effect. Since $\bar{\beta} = O(\epsilon^2)$ by comparing hydrostatics with the ambient environment pressure, we let

$$C = C_o + \epsilon^2 c(x, z, t), \quad \rho = \frac{1}{1 + \epsilon^2 V c(x, z, t)}, \quad \bar{\beta} = \epsilon^2 \beta.$$

At leading order, we find from Eqs. (13) and (14) that

$$p_{oz} = -\cos\alpha, \quad c_{ozz} + \beta V p_{ozz} = 0.$$

Since there is no mass flux through the plate $z=0$ or through the interface, we can integrate the conservation of concentration equation once to find

$$c_{oz} = -\beta V p_{oz} = \beta V \cos\alpha,$$

which gives $c_o = z\beta V \cos\alpha + \bar{c}_o(x, t)$. From the normal stress condition (17) the leading-order pressure is of the form

$$p_o(x, z, t) = (h - z)\cos\alpha - h_{xx}.$$

The leading-order contribution from Eq. (12) gives

$$u_o(x, z, t) = -\sin\alpha \frac{z}{2}(z - 2h).$$

From conservation of mass (11), we find that

$$w_o = -\frac{z^2}{2}(h_x \sin\alpha).$$

At $O(\epsilon)$, we find the following equations from Eq. (14):

$$\frac{1}{\text{Pe}}[c_{1z} + \beta V p_{1z}]_o^h = \int_0^h \bar{c}_{ot} + u_o \bar{c}_{ox} + w_o c_{oz} dz, \quad (\text{A5})$$

which, to conserve mass at $z=0$ and $z=h$, require

$$\bar{c}_{ot} + \left[\frac{h^2}{3}(\sin\alpha)\right] \bar{c}_{ox} = \frac{1}{12} h^2 h_x \beta V \sin 2\alpha. \quad (\text{A6})$$

Note that in addition that the kinematic boundary condition becomes

$$h_t + h^2 h_x \sin\alpha = O(\epsilon), \quad (\text{A7})$$

which we shall use below to simplify the next-order corrections (see Ref. 37 for a single component derivation).

To find the correction to the concentration, vertical momentum conservation requires that $p_z = w_{1zz} = -\sin\alpha h_x$, which gives

$$\begin{aligned} \frac{1}{\text{Pe}} c_{1z} = \frac{\beta V h_x}{\text{Pe}} \sin\alpha + \left\{ \sin\alpha \left[\frac{z^2 h}{2} - \frac{z h^2}{3} - \frac{z^3}{6} \right] \right\} \bar{c}_{ox} \\ + \frac{\beta V \sin 2\alpha h_x}{12} (h^2 z - z^3), \end{aligned}$$

so

$$\begin{aligned} c_1 = \bar{c}_1(x, t) + \beta V h_x \sin\alpha z - \frac{\text{Pe} \sin\alpha}{24} [z(z - 2h)]^2 \bar{c}_{ox} \\ + \frac{\beta V \sin 2\alpha h_x}{24} \left[h^2 z^2 - \frac{z^4}{2} \right]. \end{aligned} \quad (\text{A8})$$

From the $O(\epsilon)$ correction term to the x -momentum Eq. (12) we find that

$$u_1 = (p_{ox}) \frac{z(z - 2h)}{2} + M_z [\bar{c}_{ox} + \beta V h_x \cos\alpha]. \quad (\text{A9})$$

Note that the conservation of mass Eq. (11) is used to find w_1 , which includes variations of c with respect to time,

$$w_1 = -[p_{ox}] \frac{z^3}{6} + [h p_{ox}]_x \frac{z^2}{2} - M \bar{c}_{ox} \frac{z^2}{2}. \quad (\text{A10})$$

- ¹P. L. Kapitza and S. P. Kapitza, "Wave flow of thin viscous fluid layers," *Zh. Eksp. Teor. Fiz.* **18**, 3 (1948).
- ²P. L. Kapitza and S. P. Kapitza, "Wave flow of thin fluid layers of liquid," *Zh. Eksp. Teor. Fiz.* **19**, 105 (1949).
- ³J. Liu, J. D. Paul, and J. P. Gollub, "Measurements of the primary instabilities of film flows," *J. Fluid Mech.* **250**, 69 (1993).
- ⁴H.-C. Chang, "Wave evolution on a falling film," *Annu. Rev. Fluid Mech.* **26**, 103 (1994).
- ⁵A. Oron, S. H. Davis, and S. G. Bankoff, "Long-scale evolution of thin liquid films," *Rev. Mod. Phys.* **69**, 931 (1997).
- ⁶C. Ruyer-Quil and P. Manneville, "Further accuracy and convergence results on the modeling of flows down inclined planes by weighted-residual approximations," *Phys. Fluids* **14**, 170 (2002).
- ⁷O. K. Matar, "Nonlinear evolution of thin free viscous films in the presence of soluble surfactant," *Phys. Fluids* **14**, 4216 (2002).
- ⁸L. Onsager, "Reciprocal relations in irreversible processes. I," *Phys. Rev.* **37**, 405 (1931).
- ⁹L. Onsager, "Reciprocal relations in irreversible processes. II," *Phys. Rev.* **38**, 2265 (1931).
- ¹⁰S. R. de Groot and P. Mazur, *Non-Equilibrium Thermodynamics* (North-Holland, Amsterdam, 1962).
- ¹¹L. D. Landau and E. M. Lifshitz, *Fluid Mechanics* (Pergamon, Oxford, 1954).
- ¹²G. I. Taylor, "Dispersion of soluble matter in solvent flowing slowly through a tube," *Proc. R. Soc. London, Ser. A* **219**, 186 (1953).
- ¹³G. I. Taylor, "Conditions under which dispersion of a solute in a stream of solvent can be used to measure molecular diffusion," *Proc. R. Soc. London, Ser. A* **225**, 473 (1954).
- ¹⁴M. P. Brenner and H. A. Stone, "Modern classical physics through the work of G. I. Taylor," *Phys. Today* **53**(5), 30 (2000).
- ¹⁵C. Eckart, "The thermodynamics of irreversible processes II. Fluid mixtures," *Phys. Rev.* **58**, 269 (1940).
- ¹⁶J. W. Cahn and J. E. Hilliard, "Free energy of a nonuniform system. I. Interfacial free energy," *J. Chem. Phys.* **28**, 258 (1958).
- ¹⁷D. D. Joseph, "Fluid dynamics of two miscible liquids with diffusion and gradient stresses," *Eur. J. Mech. B/Fluids* **9**, 565 (1990).
- ¹⁸D. M. Anderson, G. B. McFadden, and A. A. Wheeler, "Diffuse-interface methods in fluid mechanics," *Annu. Rev. Fluid Mech.* **30**, 139 (1998).
- ¹⁹J. Lowengrub and L. Truskinovsky, "Quasi-incompressible Cahn-Hilliard fluids and topological transitions," *Proc. R. Soc. London* **454**, 2617 (1998).
- ²⁰P. C. Hohenberg and B. I. Halperin, "Theory of dynamic critical phenomena," *Rev. Mod. Phys.* **49**, 435 (1977).
- ²¹V. Brandani and J. M. Prausnitz, "Two-fluid theory and thermodynamic properties of liquid mixtures: General theory," *Proc. Natl. Acad. Sci. U.S.A.* **79**, 4506 (1982).
- ²²L. K. Antanovskii, "A phase field model of capillarity," *Phys. Fluids* **7**, 747 (1995).
- ²³S. E. Bechtel, M. G. Forest, F. J. Rooney, and Q. Wang, "Thermal expansion models of viscous fluids based on limits of free energy," *Phys. Fluids* **15**, 2681 (2003).
- ²⁴U. Thiele, S. Madruga, and L. Frastia, "Decomposition driven interface evolution for layers of binary mixtures. I. Model derivation and stratified base states," *Phys. Fluids* **19**, 122106 (2007).
- ²⁵M. Bourich, M. Hasnaoui, M. Mamou, and A. Amahmid, "Soret effect inducing subcritical and Hopf bifurcations in a shallow enclosure filled with a clear binary fluid or a saturated porous medium: A comparative study," *Phys. Fluids* **16**, 551 (2004).
- ²⁶A. Oron and A. A. Nepomnyashchy, "Long-wavelength thermocapillary instability with the Soret effect," *Phys. Rev. E* **69**, 016313 (2004).
- ²⁷A. Podolny, A. Oron, and A. A. Nepomnyashchy, "Long-wave Marangoni instability in a binary-liquid layer with deformable interface in the presence of Soret effect: Linear theory," *Phys. Fluids* **17**, 104104 (2005).
- ²⁸A. Podolny, A. Oron, and A. A. Nepomnyashchy, "Linear and nonlinear theory of long-wave Marangoni instability with the Soret effect at finite Biot numbers," *Phys. Fluids* **18**, 054104 (2006).
- ²⁹S. Shklyaev, A. A. Nepomnyashchy, and A. Oron, "Three-dimensional oscillatory long-wave Marangoni convection in a binary liquid layer with the Soret effect: Bifurcation analysis," *Phys. Fluids* **19**, 072105 (2007).
- ³⁰A. Podolny, A. A. Nepomnyashchy, and A. Oron, "Marangoni convection in binary and nano-fluids," *Bulletin of American Physical Society, Proceedings of the 60th Annual Meeting of the Division of Fluid Dynamics* (American Physical Society, College Park, 2007), Vol. 52.
- ³¹The results presented here were not sensitive to gate height and dimples were observed for a variety of film thicknesses.
- ³²A. E. Hosoi and J. W. M. Bush, "Evaporative instabilities in climbing films," *J. Fluid Mech.* **442**, 217 (2001).
- ³³L. Grunberg and A. H. Nissan, "Mixture law for viscosity," *Nature (London)* **164**, 799 (1949).
- ³⁴A. Hubel, N. Bidault, and B. Hammer, "Transport characteristics of glycerol and propylene glycerol in an engineered dermal replacement," *Proceedings of IMECE 2002* (American Society of Mechanical Engineers, New Orleans, 2002).
- ³⁵Due to our choice of the capillary length scale, the Marangoni number measures the relative difference in bulk surface tensions compared to the mixture value.
- ³⁶S. W. Joo and S. H. Davis, "Instabilities of three-dimensional viscous falling films," *J. Fluid Mech.* **242**, 529 (1992).
- ³⁷D. J. Benney, "Long waves on liquid films," *J. Math. Phys.* **45**, 150 (1966).